

DUO-CHEK®

High Performance Check Valves



CRANE®

Energy Flow Solutions


Duo-Chek – The High Performance Non-Slam Check Valve

Duo-Chek high performance non-slam check valves are the original Mission wafer check valves introduced to the market in the late 50's. They are available in the sizes, pressure classes and configurations you need to meet the most demanding of applications. Our product range includes, but is not limited to,

- Sizes: 2" to 72"
- ASME Pressure Class 125 through 2500
- API 6A and 6D pressure classes
- DIN, JIS, BS, AS, and ISO standards are also available.
- Wafer, lug, double flanged and extended body styles
- Configurations available in retainerless style.

Retainerless valves for critical applications without pin retainer penetration through the body are available in Wafer and are standard in Lug and Double Flange valves.

- Body Materials:
Cast Iron, WCB Cast Steel,
316 Stainless Steel. All alloys.
- Resilient Seat Materials:
EPDM, Buna-N, Neoprene,
Refrigeration-grade elastomer, Viton
- Integral and overlaid metal seats also available
- End Connections:
Raised Face, Plain Face, Ring Joint,
Weld-End, Hub-End.



Industry Standards*

API 594	Valve Design
API 598	Valve Pressure Testing & Inspection
ASME B16.5 & B16.47	Flanges
ASME B16.34	Pressure / Temperature Ratings
API 6D	Pipeline Valves
API 6A	Production Valves
(PED) 97/23/EC	Pressure Equipment Directive

*Duo-Chek meets or exceeds these industry standards.


Specify the Duo-Chek ...to your advantage

Leading engineering specifiers specify the Duo-Chek for check valve applications because it provides high performance. Extensive research and testing with demonstrated performance has earned worldwide recognition, unmatched in the industry.


The Duo-Chek wafer valve design is generally stronger, lighter, smaller, more efficient and less expensive than conventional swing check valves. Its design meets API 594 which is approximately one fourth the face to face dimension and 15% to 20% the weight, on most popular sizes, making them less expensive than a swing check valve. It is much easier to install between standard gaskets and line flanges. The savings compound during installation due to ease of handling and only one set of flange studs is required. Therefore, it is more cost effective to install, and also to maintain.




The Duo-Chek also offers special design features that make it a high performance non-slam check valve. These include a scrub-free opening, and in most sizes a unique independent spring design as well as an independent plate support system. These features may not be found in other check valves. Other configurations offered include lug, double flange and extended body.



Plates in closed position. Top view.



Heel opens first as flow begins.



Plates fully opened (85°)





Plate toe closes first as flow decreases.




Plates fully seated for bubble-tight shutoff.

The innovative dual-plate design of the Duo-Chek employs two spring-loaded plates (disc halves) suspended on a central vertical hinge pin. As flow begins, the plates open in response to a resultant force (F) which acts as the center of the sealed surface area. The contact point of the reacting spring leg's force (F_s) acts beyond the center of the plate area, causing the heel to open first. This prevents rubbing of the seal surface prior to normal plate opening, eliminating wear.

As the velocity of flow decreases, torsion spring action reacts automatically. This moves the plates closer to the body seats, reducing the distance and time of travel for closure. By having the plates closer to the body seats at the time of flow reversal, the valve dynamic response is greatly accelerated. This dramatically reduces the water hammer effect for non-slam performance.

At closing, the point of spring force causes the toe of the plates to close first. This prevents dragging of the heels of the plates and maintains seal integrity for much longer periods.

Independent Spring Design



A spring design of the Duo-Chek (sizes 6" and larger) allows higher torque to be exerted against each plate with independent closing in response to the process stream. Testing has proved this action provides up to 25% improvement

in valve life and 50% reduction in water hammer.

Each of the dual plates has its own spring or springs, which provide independent closing action. These independent springs undergo less angular deflection, only 140° as compared to 350° for conventional springs with two legs.

Independent Plate Suspension Design

The Duo-Chek unique hinge design reduces friction forces by 66%, which improves valve response significantly. Support sleeves are inserted through the outboard hinges so that the upper hinge is independently supported by the lower sleeve during valve operation. This allows both plates to close at the same time for quick response, and excellent dynamic performance.

Features and Benefits

Features	Benefits
Lightweight and Compact Wafer Design	Installs between mating flanges with 10 to 20% the weight of flanged swing checks in popular sizes - Saves money in initial valve cost and provides lower installation cost.
Dual Plate, Flat Seat Design	Plate heel is lifted first by design to prevent seat wear. Employs two spring-loaded plates with flat seats - Gives superior performance and bubble-tight shutoff with resilient seats.
Independent Spring Action	Maximum deflection of 140°, provides improved valve response and longer life- Saves money with longer valve life and improved system performance by reducing water hammer.
Independent Plate Suspension with Unique Hinge Design (larger sizes)	Improves valve response and reduces friction forces by 66% - Further assurances of non-slam performance with faster valve response.
Simple, External Body Geometry	Configuration simplifies valve insulation - Saves money.
Variety of Body Designs Available - Lug and Double Flange	Provides options to suit application needs - Eases your selection process by utilizing the industry leader as your single source.
Wide Variety of Materials	Versatility for many services - Satisfies more application needs.
Flexibility in Installation Position	Provides more rigidity than pipe, eliminating concerns of pipe bending loads of flanged valves - Safety against thermal or seismic catastrophes.
Body Strength and Rigidity	Some sizes suitable for horizontal or vertical up positions - Simplifies piping design, eliminates constraints that swing checks create.
Retainerless Duo-Chek Design Eliminates Body Penetrations	For critical service applications, prevents possible escape of unwanted and/or hazardous materials to atmosphere - Safety in critical services eliminates and/or environmental concerns. Standards in Lug and Double Flange Designs.
Vertical Hinged Design	In horizontal position flow allows plates to function freely and full open under lower flow conditions as compared to swing check - Reduces pressure loss, improves dynamic response and eliminates valve chatter.
Special Valves Meet Market Needs: <ul style="list-style-type: none"> • NSF-61 Approval • UL Listed • Rubber Lined • Hub Ends (Grayloc®) • Weld Ends 	Wide size range, pressure range and added options allow further market needs to be met - Reliance on world's largest wafer check line to supply more needs.

Applications

A wide variety of body designs, materials, and trim make Duo-Chek valves exceptionally versatile and suitable for a multitude of liquid and gas fluid applications.

Some of the major markets and typical applications are depicted here.

Petroleum Refining

Hydrogen
Cracking
Steam
Crude Oil
Gasoline
Visbreakers
Naphtha
Sulfur

Oil and Gas Production

Centrifugal Compressor Discharge
Fire Water Lines
Oil/Steam Separation
Steam and CO₂ Injection
Gas/Oil Gathering Systems
Flowlines
Wellheads

Petrochemicals

Ethylene
Propylene
Steam
Reboilers
Gases

Chemicals

Chlorine
Phosgene
Aromatics
Polymers
Acids
Air Separation
Caustics

Power Generation

Steam
Condensate
Boiler Feed Pumps
Cooling Towers
Service Water Recirculators
River Water Intake

Steel/Primary Metals

Quench Lines
De-Scaling
Continuous Casters
Steam
Condensate
Strippers
Electro-Galvanizing



Applications

**Marine**


Oil Tankers
Tanker Loading Terminals
Offshore Platforms
Sub-Sea Manifolds
Terminal Transfer Lines
Barge Unloading Lines
Shipboard Services

Water and Wastewater

Distribution Lines
Pumping Stations
Sewage Plant Blower Discharge
Chemical Treatment
Fire Protection Systems
HVAC Systems

Pulp and Paper

Bleaching Lines
Black Liquor
Green Liquor
White Water
Steam
Chemical Recovery



Valve Configurations

Style G

Wafer

Sizes 2" – 72"

- ASME Classes 125 – 2500
- Wafer Design
- Dimensions pages 7–8



Style H

Retainerless Wafer

Sizes 2" – 72"

- ASME Classes 150 – 2500
- Dimensions pages 7–8



Retainerless Wafer Double Flange Valves

Sizes 8" – 72"

- ASME Classes 150 – 900
- Sizes & Dimensions page 10



Retainerless Wafer Lug Valves

Sizes 2" – 24"

- ASME Classes 150 – 2500
- Sizes & Dimensions page 11



Style X


Extended Body Wafer

Sizes 6" – 54"

- ASME Classes 150 – 2500
- Designed for extremely fast opening conditions
- Sizes & Dimensions page 16



Style G Installation Dimensions



Style G wafer style body valves are designed with flangeless bodies with relatively short face-to-face dimensions. They are clamped between mating flanges which are connected by studs and nuts.

ASME Class 125 (Cast Iron valves only)

Size	A		B		C		D		Weight	
	in	mm	in	mm	in	mm	in	mm	lbs.	kg.
2"	50	4 1/8	105	2 1/8	54	2 1/16	52	—	4	1.8
2 1/2"	65	4 7/8	124	2 1/8	54	2 15/32	63	—	6	2.7
3"	80	5 5/8	137	2 1/4	57	3 1/16	78	5/8	16	7
4"	100	6 7/8	175	2 1/2	64	4	102	1	25	12
5"	125	7 3/4	197	2 3/4	70	5	127	1 5/16	33	15
6"	150	8 3/4	222	3	76	6 1/16	154	1 15/16	35	20
8"	200	11	279	3 3/4	95	8	203	3 1/16	54	40
10"	250	13 3/8	340	4 1/4	108	10	254	3 3/8	70	65
12"	300	16 1/8	410	5 5/8	143	11 15/16	303	3 3/16	83	110
14"	350	17 3/4	451	7 1/4	184	12 1/2	318	3 1/16	83	183
16"	400	20 1/4	514	7 1/2	191	15	381	4 1/4	113	255
18"	450	21 5/8	549	8	203	16 7/8	429	5 5/8	137	315
20"	500	23 7/8	606	8 3/8	213	18 13/16	478	6 3/16	160	380
24"	600	28 1/4	718	8 3/4	222	22 5/8	575	8 1/4	210	575
30"	750	34 3/4	883	12	305	29 1/4	743	9 9/16	229	1070
36"	900	41 1/4	1048	14 1/2	368	35	889	12 5/16	303	1962
42"	1050	48	1219	17	432	41	1041	15	381	2800
48"	1200	54 1/2	1384	20 5/8	524	47	1194	16 3/4	425	3920
54"	1350	61	1549	21 1/4	540	51 1/2	1308	19 3/4	502	6172
60"	1500	67 1/2	1715	26	660	56	1422	—	7800	3538
66"	1650	74 1/4	1886	31	787	65 1/4	1657	—	12000	5443
72"	1800	80 3/4	2051	36	914	68	1727	—	14000	6350

ASME Class 150

Size	A		B		C		D		Weight	
	in	mm	in	mm	in	mm	in	mm	lbs.	kg.
2"	50	4 1/8	105	2 3/8	60	1 15/16	49	—	—	6
2 1/2"	65	4 7/8	124	2 3/8	67	2 11/32	60	—	—	10
3"	80	5 5/8	137	2 7/8	73	2 29/32	74	1 1/4	6	13
4"	100	6 7/8	175	2 7/8	73	3 59/64	97	5/8	16	17
5"	125	7 3/4	197	3 3/8	86	4 13/16	122	7/8	22	27
6"	150	8 3/4	222	3 3/8	98	5 49/64	146	1 3/8	35	35
8"	200	11	279	5	127	7 5/8	194	2 1/8	54	70
10"	250	13 3/8	340	5 1/4	146	9 9/16	243	2 3/4	70	106
12"	300	16 1/8	410	7 1/8	181	11 3/8	289	3 1/4	83	172
14"	350	17 3/4	451	7 1/4	184	12 1/2	318	3 1/4	83	200
16"	400	20 1/4	514	7 1/2	191	15	381	4 7/16	113	275
18"	450	21 5/8	549	8	203	16 7/8	429	5 3/8	137	315
20"	500	23 7/8	606	8 3/8	213	18 13/16	478	6 3/16	160	435
24"	600	28 1/4	718	8 3/4	222	22 5/8	575	8 1/4	210	620
26"	650	30 1/2	775	14	356	24 1/4	616	8	203	1555
30"	750	34 3/4	883	13	330	29 1/4	743	9	229	1230
36"	900	41 1/4	1048	15 1/4	387	35	889	11 15/16	303	2017
42"	1050	48	1219	17	432	41	1041	15	381	2800
48"	1200	54 1/2	1384	20 5/8	524	47	1194	16 3/4	425	3920
54"	1350	61	1549	21 1/4	540	51 1/2	1308	19 3/4	502	6172
60"	1500	67 1/2	1715	26	660	56	1422	—	7800	3538
66"	1650	74 1/4	1886	31	787	65 1/4	1657	—	12000	5443
72"	1800	80 3/4	2051	36	914	68	1727	—	14000	6350

Duo-Cheks are available in accordance with DIN, BS, JIS, AS and ISO Dimensions. For other sizes and pressure classes contact factory. Class 125 face-to-face dimensions 2 1/2"-12" are thinner than the requirements of API 594.

Style G Installation Dimensions, cont'd

ASME Class 250 (Cast Iron valves only)

Size		A		B		C		D		Weight	
in	mm	in	mm	in	mm	in	mm	in	mm	lbs.	kg.
2"	50	4 3/8	111	2 1/8	54	1 15/16	49	3/8	2	5	2.3
2 1/2"	65	5 1/8	130	2 2/8	60	2 11/32	60	1/8	10	11	5
3"	80	5 7/8	149	2 2/8	67	2 29/32	74	1/4	14	11	5
4"	100	7 1/8	181	2 2/8	67	3 53/64	97	1/16	14	14	6.4
5"	125	8 1/2	216	3 1/4	83	4 13/16	122	1	25	29	13.2
6"	150	9 7/8	251	3 3/4	95	5 49/64	146	1 1/2	38	35	16
8"	200	12 1/8	308	5	127	7 5/8	194	2 1/8	54	75	34
10"	250	14 1/4	362	5 1/2	140	9 9/16	243	3 1/16	80	113	51
12"	300	16 5/8	422	7 1/8	181	11 3/8	289	3 1/4	83	174	79
14"	350	19 1/8	486	8 3/4	222	12 1/2	318	3 3/16	81	299	136
16"	400	21 1/4	540	9 1/8	232	14 5/16	364	4 1/8	105	380	172
18"	450	23 1/2	597	10 1/8	264	16 7/8	429	4 13/16	122	510	231
20"	500	25 1/4	654	11 1/2	292	17 15/16	456	5 5/8	136	593	269
24"	600	30 1/2	775	12 1/2	318	21 9/16	548	7 1/16	179	1010	458
30"	750	37 1/2	953	14 1/2	368	28 3/4	730	8 13/16	224	1880	853
36"	900	44	1118	19	483	35	889	11 1/16	294	3573	1608
42"	1050	50 1/4	1289	22 1/8	568	41	1041	14 1/4	375	5780	2622
48"	1200	58 1/4	1492	24 1/4	629	47	1194	16 1/2	419	6572	2981

ASME Class 300

Size		A		B		C		D		Weight	
in	mm	in	mm	in	mm	in	mm	in	mm	lbs.	kg.
2"	50	4 3/8	111	2 1/8	60	1 15/16	49	—	—	7	3
2 1/2"	65	5 1/8	130	2 2/8	67	2 11/32	60	—	—	11	5
3"	80	5 7/8	149	2 2/8	73	2 29/32	74	1/4	6	15	7
4"	100	7 1/8	181	2 7/8	73	3 53/64	97	5/8	16	18	8
5"	125	8 1/2	216	3 3/8	86	4 13/16	122	7/8	22	35	16
6"	150	9 7/8	251	3 7/8	98	5 49/64	146	1 1/8	35	45	20
8"	200	12 1/8	308	5	127	7 5/8	194	2 1/8	54	82	37
10"	250	14 1/4	362	5 1/2	146	9 9/16	243	2 3/8	70	125	57
12"	300	16 5/8	422	7 1/8	181	11 3/8	289	3 1/4	83	200	91
14"	350	19 1/8	486	8 3/4	222	12 1/2	318	3 3/16	81	325	147
16"	400	21 1/4	540	9 1/8	232	14 5/16	364	4 1/8	105	415	188
18"	450	23 1/2	597	10 1/8	264	16 7/8	429	4 13/16	122	555	252
20"	500	25 1/4	654	11 1/2	292	17 15/16	456	5 5/8	143	725	329
24"	600	30 1/2	775	12 1/2	318	21 9/16	548	7 1/16	179	1100	499
26"	650	32 1/8	835	14	356	24 3/8	619	8	203	1605	728
30"	750	37 1/2	953	14 1/2	368	28 3/4	730	9 1/16	230	2050	930
36"	900	44	1118	19	483	35	889	11 1/16	284	3573	1621
42"	1050	50 1/4	1289	22 1/8	568	41	1041	14 1/4	375	5780	2622
48"	1200	58 1/4	1492	24 1/4	629	47	1194	16 1/2	419	6572	2981

ASME Class 600

Size		A		B		C		D		Weight	
in	mm	in	mm	in	mm	in	mm	in	mm	lbs.	kg.
2"	50	4 3/8	111	2 1/8	60	1 15/16	49	—	—	7	3
2 1/2"	65	5 1/8	130	2 2/8	67	2 11/32	60	1/8	3	11	5
3"	80	5 7/8	149	2 2/8	73	2 29/32	74	1/4	6	15	7
4"	100	7 5/8	194	3 1/8	79	3 53/64	97	7/8	22	26	12
5"	125	9 1/2	241	4 1/8	105	4 13/16	122	1	25	50	22.7
6"	150	10 1/2	267	5 1/8	137	5 49/64	146	1 7/16	36	80	36
8"	200	12 5/8	321	6 1/2	165	7 5/8	194	2	51	135	61
10"	250	15 3/4	400	8 3/8	213	9 9/16	243	2 3/32	58	238	108
12"	300	18	457	9	229	11 3/8	289	3 15/32	88	333	151
14"	350	19 3/8	492	10 3/4	273	12 1/2	318	2 3/4	70	455	206
16"	400	22 1/4	565	12	305	14 5/16	364	4 5/16	110	640	290
18"	450	24 1/8	613	14 1/4	362	16 1/8	410	3 11/16	94	890	404
20"	500	26 7/8	683	14 1/2	368	17 15/16	456	5 5/16	135	1120	508
24"	600	31 1/8	791	17 1/4	438	21 9/16	548	6 9/16	167	2040	925
26"	650	34 1/8	867	18	547	24	610	7 1/4	184	2530	1148
30"	750	38 1/4	972	19 1/8	505	28 3/4	730	9 9/16	243	3375	1531
36"	900	44 1/2	1130	25	635	33 3/4	857	11 15/16	303	6300	2858
42"	1050	51	1295	27 5/8	702	39 1/2	1003	14 1/4	362	8447	3832

ASME Class 900

Size		A		B		C		D		Weight	
in	mm	in	mm	in	mm	in	mm	in	mm	lbs.	kg.
2"	50	5 5/8	143	2 3/4	70	1 11/16	43	—	—	14	6
2 1/2"	65	6 1/2	165	3 1/4	83	2 1/8	54	1/16	2	16	7
3"	80	6 5/8	168	3 1/4	83	2 5/8	67	5/16	8	24	11
4"	100	8 1/8	206	4	102	3 7/16	87	9/16	14	40	18
5"	125	9 3/4	248	—	—	4 5/16	110	—	—	—	—
6"	150	11 1/8	283	6 1/4	159	5 3/16	132	1 1/16	27	110	50
8"	200	13 1/8	352	8 1/8	206	6 13/16	173	1 13/32	36	219	99
10"	250	17 1/8	435	9 3/4	248	8 1/2	216	1 11/16	43	397	180
12"	300	20 1/2	521	12	305	10 1/8	257	2 1/4	57	725	329
14"	350	22 3/4	578	14	356	11 1/2	292	2	51	948	430
16"	400	25 1/4	641	15 1/8	384	12 13/16	325	2 5/8	67	1380	627
18"	450	27 3/4	705	18 7/16	468	13 3/4	349	2 11/16	68	1900	863
20"	500	29 3/4	756	21	533	14 3/4	375	4	102	2750	1247
24"	600	35 1/2	902	22	559	15 1/8	384	4 1/8	105	5860	2658

ASME Class 1500

Size		A		B		C		D		Weight	
in	mm	in	mm	in	mm	in	mm	in	mm	lbs.	kg.
2"	50	5 3/4	146	2 3/4	70	1 11/16	43	—	—	15	7
2 1/2"	65	6 5/8	168	3 1/4	83	2 1/8	54	1/16	2	22	10
3"	80	7 3/4	197	3 3/8	86	2 5/8	67	1/4	6	31	14
4"	100	9 1/4	235	4 1/8	105	3 7/16	87	7/16	11	54	25
5"	125	11	279	—	—	4 5/16	110	—	—	—	—
6"	150	12 1/2	318	6 1/4	159	5 3/16	132	1 1/16	27	190	86
8"	200	15 1/4	387	8 1/8	206	6 13/16	173	1 11/16	43	285	129
10"	250	18 3/4	476	10	254	8 1/2	216	1 13/16	46	502	228
12"	30										

Style H[†] Retainerless Check Valves

High Performance Check Valve for Critical Applications




For critical applications, Style H retainerless Duo-Chek valves feature a one-piece body with no pin retainer penetration through the body.

These high performance valves utilize the same internal design of other Duo-Chek valves with all the unique features and advantages built into them.

Item No.	Part No.
1	Body
2	Plate
3	Seal
4	Stop Pin
5	Hinge Pin
6	Spring*
7	Pin Insert
8	Snap Ring
9	Body Bearing
10	Plate Bearing
11	Spring Bearing

* Independent spring in valve sizes 6" and larger.



This view is rotated 90° to show the actual operating position of the valve. The pin must be vertical for horizontal flow.

Because Retainerless Duo-Chek valves have no body penetrations potential leak paths through the valve are eliminated. This makes the Retainerless Duo-Chek ideally suited to meet the following critical service applications:

- Hydrocarbon processing
- Chemical processing
- Any industry concerned with fire hazards or environmental safety

Key features of the Duo-Chek Style H wafer check valve include:

- A wide selection of body and plate materials
- A choice of metal-to-metal or resilient sealing

- A full range of pressure classes and sizes
- A variety of end connections
- Designs available include wafer, lug and double flange.
- Internals easily removed for field replacement under normal inspections and maintenance procedures

The advanced design of the Duo-Chek provides many operational benefits to the user, which combined with its more compact size and lower weight, make the Duo-Chek Style H an excellent alternative to a standard swing check valve.


Remarkable advantages include:

- Independent spring action (on 6" and larger) and plate suspension on larger valves
- Free release flat seats
- Springs provide superior response to flow reversal or deceleration
- Minimal water hammer
- Savings in purchase price and installation costs compared to a conventional swing check valve
- Single body design with no body cartridge


[†] Installation dimensions for these valves are as shown on pages 7-8.

Style H Double Flange Retainerless Valve

Double Flanged Style Valves bolt up similar to a bolted cap swing check or gate valve. Double flanged versions are offered as standard on larger size valves where the lay length of the body permits installation of two heavy nuts between the flanges. These valves are standard retainerless design.



Pin must be vertical
for horizontal flow.



Flow Direction

ASME Class 150

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
8"	200	13 1/2	343	5	127	7 5/8	194	93	42
10"	250	16	406	5 3/4	146	9 9/16	243	189	86
12"	300	19	483	7 1/8	181	11 3/8	289	218	99
14"	350	21	533	7 1/4	184	12 1/2	318	274	124
16"	400	23 1/2	597	7 1/2	191	15	381	353	160
18"	450	25	635	8	203	16 7/8	428	409	185
20"	500	27 1/2	699	8 5/8	219	18 7/8	480	552	250
24"	600	32	813	8 3/4	222	22 5/8	575	860	389
30"	750	38 3/4	984	12	330	29 1/4	743	1512	687
36"	900	46	1168	14 1/2	387	35	889	2525	1145
42"	1050	53	1346	17	432	41	1041	4163	1888
48"	1200	59 1/2	1511	20 5/8	524	47	1194	5880	2667
54"	1350	66 1/4	1683	21 1/4	539	51 1/2	1308	—	—
60"	1500	73	1854	26	660	56	1422	—	—
66"	1650	80	2032	31	787	62 1/2	1588	—	—
72"	1800	86 1/2	2197	36	914	68	1727	—	—

ASME Class 300

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
12"	300	20 1/2	521	7 1/8	181	11 3/8	289	336	152
14"	350	23	584	8 3/4	222	12 1/2	318	431	195
16"	400	25 1/2	648	9 1/8	232	14 1/8	365	619	280
18"	450	28	711	10 3/8	264	16 1/8	409	850	385
20"	500	30 1/2	775	11 1/2	292	17 7/8	454	1078	488
24"	600	36	914	12 1/2	318	22 1/8	562	1516	686
30"	750	43	1092	14 1/2	368	28 3/4	730	3100	1406
36"	900	50	1270	19	483	35	864	4650	2109
42"	1050	50 3/4	1289	22 3/8	568	41	1041	8670	3932
48"	1200	57 3/4	1467	24 3/4	629	47	1193	9950	4513
54"	1350	65 1/4	1657	27 1/4	692	51 1/2	1308	—	—
60"	1500	73	1854	32 1/2	826	56	1422	—	—

Notes:

- Sizes not available in double flange design are offered as lug body design, see page 11.
- Please consult factory for other sizes and pressure classes available.
- Consult factory for weights not shown.

ASME Class 600


Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
12"	300	22	559	9	229	11 3/8	289	612	277
14"	350	23 3/4	603	10 3/4	273	12 1/2	318	682	309
16"	400	27	685	12	305	14 1/8	365	951	430
18"	450	29 1/4	743	14 1/4	362	16 1/8	409	1221	553
20"	500	32	813	14 1/2	368	18	457	1606	728
24"	600	37	940	17 1/2	445	21 1/16	548	2451	1111
30"	750	44 1/2	1130	19 7/8	505	28 3/4	730	3825	1735
36"	900	51 3/4	1314	25	635	33 3/4	857	6057	2747
42"	1050	55 1/4	1403	27 5/8	702	39 1/2	1003	9985	4529
48"	1200	62 3/4	1594	31	787	36	914	12600	5715

ASME Class 900


Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
12"	300	24	610	11 1/2	292	10 1/8	257	770	349
14"	350	25 1/4	641	14	356	11 1/2	292	1240	561
16"	400	27 3/4	705	15 1/8	384	12 7/8	327	1210	548
18"	450	31	787	17 3/4	451	14 1/2	368	1845	835
20"	500	33 3/4	857	17 3/4	451	18	457	3940	1787
24"	600	41	1041	19 1/2	495	21 1/2	546	4175	1893
30"	750	48 1/2	1222	25	635	26	660	6500	2948
36"	900	57 1/2	1461	28	711	31	787	—	—
42"	1050	61 1/2	1562	31 1/2	800	36	914	—	—

Style H Lug Retainerless Valve


Lug Style valves cover the bolting the entire length of the body. Lug valves are furnished in scallop and full body designs. Scallop is furnished whenever possible to keep weight to a minimum. These valves are standard retainerless design. Lug valves are furnished with thru-hole bolting in accordance with API 594. Threaded bolt holes are available when specified, however, valve should not be used for dead end service.



Scallop



Full Body



Pin must be vertical
for horizontal flow.

ASME Class 150

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
2"	50	6	152	2 3/8	60	1 15/16	49	17	8
2 1/2"	65	7 1/2	191	2 3/8	67	2 11/32	60	17	8
3"	80	8 1/4	210	2 7/8	73	2 29/32	74	17	8
4"	100	9	229	2 7/8	73	3 53/64	97	28	13
5"	125	10	254	3 3/8	86	4 13/16	122	36	16
6"	150	11	279	3 7/8	98	5 49/64	146	48	22

ASME Class 300

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
2"	50	6	152	2 3/8	60	1 15/16	49	18	8
2 1/2"	65	7 1/2	191	2 3/8	67	2 11/32	60	22	10
3"	80	8 1/4	210	2 7/8	73	2 29/32	74	30	14
4"	100	10	254	2 7/8	73	3 53/64	97	36	16
5"	125	11	279	3 3/8	86	4 13/16	122	51	23
6"	150	12 1/2	318	3 7/8	98	5 49/64	146	84	38
8"	200	15	381	5	127	7 5/8	194	135	61
10"	250	17 1/2	445	5 3/4	146	9 9/16	243	270	123

ASME Class 600

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
2"	50	6	152	2 3/8	60	1 15/16	49	18	8
2 1/2"	65	7 1/2	191	2 3/8	67	2 11/32	60	22	10
3"	80	8 1/4	210	2 7/8	73	2 29/32	74	30	14
4"	100	10 3/4	273	3 1/8	79	3 53/64	97	50	23
6"	150	14	356	5 3/8	137	5 49/64	146	183	83
8"	200	16 1/2	419	6 1/2	165	7 5/8	194	295	134
10"	250	20	508	8 5/8	213	9 9/16	243	540	245

ASME Class 900

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
2"	50	8 1/2	216	2 3/4	70	1 15/16	43	37	17
3"	80	9 1/2	241	3 1/4	83	2 5/8	67	57	26
4"	100	11 1/2	292	4	102	3 5/16	87	98	45
6"	150	15	381	6 1/4	159	5 5/16	132	252	114
8"	200	18 1/2	470	8 1/8	206	6 13/16	173	441	200
10"	250	21 1/2	546	9 1/2	241	8 1/2	216	787	357

ASME Class 1500

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
2"	50	8 1/2	216	2 3/4	70	1 15/16	43	37	17
3"	80	10 1/2	267	3 1/4	83	2 5/8	67	70	32
4"	100	12 1/4	311	4	102	3 5/16	87	112	51
6"	150	15 1/2	394	6 1/4	159	5 5/16	132	262	119
8"	200	19	483	8 1/8	206	6 13/16	173	488	221
10"	250	23	584	9 1/4	248	8 1/2	216	917	416
12"	300	26 1/2	673	12	305	10 1/8	257	1425	646
14"	350	29 1/2	749	14	356	11 1/2	292	2045	928
16"	400	32 1/2	826	15 1/8	384	12 13/16	325	2600	1179
18"	450	36	914	18 1/16	468	13 3/4	349	3883	1761
20"	500	38 3/4	984	21	533	14 1/4	348	5700	2580
24"	600	46	1168	22	559	15 1/8	384	7150	3236

ASME Class 2500

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
2"	50	9 1/4	235	2 3/4	70	1 15/16	43	48	22
3"	80	12	305	3 3/8	86	2 5/8	67	93	42
4"	100	14	356	4 1/8	105	3 5/16	87	152	69
6"	150	19	483	6 1/4	159	5 5/16	132	386	175
8"	200	21 3/4	552	8 1/8	206	6 13/16	173	682	309
10"	250	26 1/2	673	10	254	8 1/2	216	1233	559
12"	300	30	762	12	305	10 1/8	257	1881	853

- Consult factory for additional sizes and pressure classes.

DIN Valve Outside Diameter of Body

PN 6, 10, 16 (ASME Class 150)

Size		PN	A (DIN)*	
in	mm		mm	in
2"	50	6	98	3 27/32
		10	109	4 9/32
		16	109	4 9/32
2 1/2"	65	6	118	4 5/8
		10	129	5 1/16
		16	129	5 1/16
3"	80	6	134	5 1/4
		10	144	5 21/32
		16	144	5 21/32
4"	100	6	154	6 1/16
		10	164	6 7/16
		16	164	6 7/16
5"	125	6	184	7 7/32
		10	194	7 5/8
		16	194	7 5/8
6"	150	6	209	8 7/32
		10	220	8 21/32
		16	220	8 21/32
8"	200	6	264	10 3/8
		10	275	10 13/16
		16	275	10 13/16
10"	250	6	319	12 17/32
		10	330	13
		16	331	13 1/2
12"	300	6	375	14 3/4
		10	380	14 15/16
		16	386	15 3/16
14"	350	6	425	16 23/32
		10	440	17 5/16
		16	446	17 17/32
16"	400	6	475	18 11/16
		10	491	19 5/16
		16	498	19 19/32
18"	450	10	541	21 1/32
		16	558	21
20"	500	6	580	22 13/16
		10	596	23 7/16
		16	620	24 13/16
24"	600	6	681	26 25/32
		10	698	27 15/32
		16	737	29
28"	700	6	786	30 15/16
		10	813	32
		16	807	31 3/4
32"	800	6	893	35 5/32
		10	920	36 7/32
		16	914	35 15/16
36"	900	6	993	39 3/32
		10	1020	40 5/32
		16	1014	39 29/32
40"	1000	6	1093	43 1/2
		10	1127	44 3/8
		16	1131	44 1/2
48"	1200	6	1310	51 9/16
		10	1344	52 15/16
		16	1345	52 15/16

PN 25, 40 (ASME Class 300)

Size		PN	A (DIN)*	
in	mm		mm	in
2"	50	25	109	4 3/32
		40	109	4 3/32
2 1/2"	65	25	129	5 1/16
		40	129	5 1/16
3"	80	25	144	5 21/32
		40	144	5 21/32
4"	100	25	170	6 11/16
		40	170	6 11/16
5"	125	25	196	7 11/16
		40	196	7 11/16
6"	150	25	226	8 7/8
		40	226	8 7/8
8"	200	25	286	11 1/4
		40	293	11 17/32
10"	250	25	343	13 1/2
		40	355	13 31/32
12"	300	25	403	15 27/32
		40	420	16 17/32
14"	350	25	460	18 3/32
		40	477	18 3/4
16"	400	25	517	20 11/32
		40	549	21 19/32
18"	450	40	574	22 19/32
		25	627	24 11/16
20"	500	40	631	24 13/16
		25	734	28 7/8
24"	600	40	750	29 1/2

PN 160 (ASME Class 900)

Size		PN	A (DIN)*	
in	mm		mm	in
2"	50	160	121	4 3/4
2 1/2"	65	160	146	5 3/4
3"	80	160	156	6 1/8
4"	100	160	183	7 3/16
5"	125	160	220	8 27/32
6"	150	160	260	10 7/32
8"	200	160	327	12 27/32
10"	250	160	391	15 3/8
12"	300	160	461	18 1/8

PN 250 (ASME Class 1500)

Size		PN	A (DIN)*	
in	mm		mm	in
2"	50	250	126	4 15/16
2 1/2"	65	250	156	6 1/8
3"	80	250	173	6 25/32
4"	100	250	205	8 1/16
5"	125	250	245	9 5/8
6"	150	250	287	11 3/32
8"	200	250	361	14 3/16
10"	250	250	445	17 1/2
12"	300	250	542	21 5/16

PN 320 (ASME Class 2500)


Size		PN	A (DIN)*	
in	mm		mm	in
2"	50	320	136	5 1/32
2 1/2"	65	320	173	6 25/32
3"	80	320	193	7 19/32
4"	100	320	232	9 1/8
5"	125	320	277	10 29/32
6"	150	320	314	12 11/32
8"	200	320	401	15 25/32
10"	250	320	492	19 11/32

PN 64, 100 (ASME Class 600)

Size		PN	A (DIN)*	
in	mm		mm	in
2"	50	64	115	4 1/2
		100	121	4 3/4
2 1/2"	65	64	140	5 1/2
		100	146	5 3/4
3"	80	64	150	5 29/32
		100	156	6 1/8
4"	100	64	176	6 29/32
		100	183	7 17/32
5"	125	64	213	8 3/8
		100	220	8 27/32
6"	150	64	250	9 13/16
		100	260	10 7/32
8"	200	64	312	12 9/32
		100	327	12 27/32
10"	250	64	367	14 7/16
		100	394	15 1/2
12"	300	64	427	16 25/32
		100	461	18 1/8
14"	350	64	489	19 1/4
		100	515	20 1/4
16"	400	64	546	21 15/32
		100	575	22 5/8
20"	500	64	660	25 31/32
		100	708	27 27/32
24"	600	64	768	30 7/32
		100	819	32 7/32

*Dimension A applies to drawing on page 7. Other dimensions for ASME Classes shown apply to these valves with DIN outside diameters.

Styles G and H Stud Selection



ASME Class 125 (Cast Iron valves only)

Valve Size	No. of Studs	B		C		
		Bolt Diameter	Flat Face	in	mm	
2"	50	4	5/8	16	5 1/4	133
2 1/2"	65	4	5/8	16	5 1/2	140
3"	80	4	5/8	16	5 3/4	146
4"	100	8	5/8	16	6 1/4	159
5"	125	8	3/4	19	6 3/4	171
6"	150	8	3/4	19	7	178
8"	200	8	3/4	19	8	203
10"	250	12	7/8	22	9	229
12"	300	12	7/8	22	10 1/2	267
14"	350	12	1	25	12 3/4	324
16"	400	16	1	25	13 1/4	337
18"	450	16	1 1/8	29	14 1/4	362
20"	500	20	1 1/8	29	15	381
24"	600	20	1 1/4	32	15 3/4	400
26"	650	24	1 1/4	32	22 3/4	578
30"	750	28	1 1/4	32	21 1/4	540
36"	900	32	1 1/2	38	26 1/4	667
42"	1050	36	1 1/2	38	28 1/2	724
48"	1200	44	1 1/2	38	33	838
54"	1350	44	1 3/4	44	35	889
60"	1500	52	1 3/4	44	-	-
66"	1650	52	1 3/4	44	-	-
72"	1800	60	1 1/8	29	-	-

ASME Class 150

Valve Size	No. of Studs	B		C		D		
		Bolt Diameter	Raised Face	in	mm	in	mm	
2"	50	4	5/8	16	5 3/4	146	6 1/4	159
2 1/2"	65	4	5/8	16	6 1/4	159	7	178
3"	80	4	5/8	16	6 3/4	171	7 1/4	184
4"	100	8	5/8	16	6 3/4	171	7 1/4	184
5"	125	8	3/4	19	7 1/2	191	8	203
6"	150	8	3/4	19	8	203	8 1/2	216
8"	200	8	3/4	19	9 1/2	241	10	254
10"	250	12	7/8	22	10 1/2	267	11	279
12"	300	12	7/8	22	12	305	12 1/2	318
14"	350	12	1	25	12 3/4	324	13 1/4	337
16"	400	16	1	25	13 1/4	337	13 3/4	349
18"	450	16	1 1/8	29	14 1/4	362	14 3/4	375
20"	500	20	1 1/8	29	15	381	15 1/2	394
24"	600	20	1 1/4	32	15 3/4	400	16 1/4	413
26"	650	24	1 1/4	32	22 3/4	578	23 1/4	591
30"	750	28	1 1/4	32	21 1/4	540	22 3/4	578
36"	900	32	1 1/2	38	26 1/4	667	39	679
42"	1050	36	1 1/2	38	28 1/2	724	-	-
48"	1200	44	1 1/2	38	33	838	-	-
54"	1350	44	1 3/4	44	35	889	-	-
60"	1500	52	1 3/4	44	-	-	-	-
66"	1650	52	1 3/4	44	-	-	-	-
72"	1800	60	1 1/8	29	-	-	-	-

Stud dimensions apply to styles G & H for Lug style thru-hole bolting design.

Styles G and H Stud Selection

ASME Classes 250 (Cast Iron valves only) & 300

Valve Size		No. of Studs	B		C		D	
			Bolt Diameter		Raised Face		Ring Joint*	
in	mm	in	mm	in	mm	in	mm	in
2"	50	8	5/8	16	6	152	6 3/4	171
2 1/2"	65	8	3/4	19	6 3/4	171	7 1/2	191
3"	80	8	3/4	19	7	178	8	203
4"	100	8	3/4	19	7 1/2	191	8 1/4	210
5"	125	8	3/4	19	8 1/4	210	9	229
6"	150	12	3/4	19	9	229	9 3/4	248
8"	200	12	7/8	22	10 1/2	267	11 1/4	286
10"	250	16	1	25	12 1/4	311	13	330
12"	300	16	1 1/8	29	14	356	14 3/4	375
14"	350	20	1 1/8	29	16	406	16 3/4	425
16"	400	20	1 1/4	32	17	432	17 3/4	451
18"	450	24	1 1/4	32	18 1/2	470	19 3/4	489
20"	500	24	1 1/4	32	19 3/4	502	20 1/2	521
24"	600	24	1 1/2	38	21 3/4	552	22 3/4	578
26"	650	28	1 5/8	41	24 1/4	616	25 1/4	641
30"	750	28	1 3/4	44	27 1/4	692	28 1/2	724
36"	900	32	2	51	32 1/4	819	35 1/2	851
42"	1050	36	2	51	36 1/2	927	37 3/4	959
48"	1200	40	2	51	40	1016	-	-

*Available in Class 300 only.

ASME Class 600

Valve Size		No. of Studs	B		C		D	
			Bolt Diameter		Raised Face		Ring Joint	
in	mm	in	mm	in	mm	in	mm	in
2"	50	8	5/8	16	6 3/4	171	7	178
2 1/2"	65	8	3/4	19	7 1/2	191	7 3/4	197
3"	80	8	3/4	19	8	203	8 1/4	210
4"	100	8	7/8	22	9 1/4	235	9 1/4	235
5"	125	8	1	25	10 3/4	273	11	279
6"	150	12	1	25	12 1/4	311	12 1/2	318
8"	200	12	1 1/8	29	14 1/4	362	14 1/2	368
10"	250	16	1 1/4	32	17	432	17 1/4	438
12"	300	20	1 1/4	32	18	457	18	457
14"	350	20	1 3/8	35	20 1/4	514	20 1/2	521
16"	400	20	1 1/2	38	22 1/4	565	22 1/2	572
18"	450	20	1 5/8	41	25 1/4	641	25 1/2	648
20"	500	24	1 5/8	41	26	660	26 1/4	667
24"	600	24	1 7/8	48	30 1/4	768	30 3/4	781
26"	650	28	1 7/8	48	31 1/2	800	32	813
30"	750	28	2	51	34 1/4	870	34 3/4	883
36"	900	28	2 1/2	64	41	1041	20 1/2	1060
42"	1050	28	2 3/4	70	47	1194	47 1/2	1207

Stud dimensions apply to styles G & H for Lug style thru-hole bolting design.

ASME Class 900

Valve Size		No. of Studs	B		C		D	
			Bolt Diameter		Raised Face		Ring Joint	
in	mm	in	mm	in	mm	in	mm	in
2"	50	8	7/8	22	8 3/4	222	8 3/4	222
2 1/2"	65	8	1	25	9 3/4	248	9 3/4	248
3"	80	8	7/8	22	9 1/4	235	9 1/4	235
4"	100	8	1 1/8	29	11	279	11	279
6"	150	12	1 1/8	29	14	356	14 1/4	362
8"	200	12	1 3/8	35	17	432	17 1/4	438
10"	250	16	1 3/8	35	19	483	19	483
12"	300	20	1 3/8	35	21 3/4	552	21 3/4	552
14"	350	20	1 1/2	38	25	635	25 1/2	648
16"	400	20	1 3/8	41	26 3/4	679	27	686
18"	450	20	1 3/8	48	30 3/4	781	31 1/2	800
20"	500	20	2	51	31 1/2	800	32 1/4	819
24"	600	20	2 1/2	64	36 3/4	933	37 1/4	946


ASME Class 1500

Valve Size		No. of Studs	B		C		D	
			Bolt Diameter		Raised Face		Ring Joint	
in	mm	in	mm	in	mm	in	mm	in
2"	50	8	7/8	22	8 3/4	222	8 3/4	222
2 1/2"	65	8	1	25	9 3/4	248	9 3/4	248
3"	80	8	1 1/8	29	10 1/2	267	10 1/2	267
4"	100	8	1 1/4	32	12	305	12	305
6"	150	12	1 3/8	35	16 3/4	425	16 3/4	425
8"	200	12	1 5/8	41	19 3/4	502	20 1/4	514
10"	250	12	1 7/8	48	23 1/4	591	23 1/2	597
12"	300	16	2	51	27	686	27 3/4	705
14"	350	16	2 1/4	57	30 1/4	768	31 1/4	794
16"	400	16	2 1/2	64	33	838	34	864
18"	450	16	2 3/4	70	38 3/4	965	39	900
20"	500	16	3	76	43 3/4	1111	44 3/4	1137
24"	600	16	3 1/2	89	48	1219	49 1/4	1251

ASME Class 2500

Valve Size		No. of Studs	B		C		D	
			Bolt Diameter		Raised Face		Ring Joint	
in	mm	in	mm	in	mm	in	mm	in
2"	50	8	1	25	10	254	10	254
2 1/2"	65	8	1 1/8	29	11 1/4	286	11 1/4	286
3"	80	8	1 1/4	32	12 1/4	311	12 1/2	318
4"	100	8	1 1/2	38	14 1/4	362	14 3/4	375
6"	150	8	2	51	20	508	20 1/2	521
8"	200	12	2	51	23 3/4	603	24	610
10"	250	12	2 1/2	64	29 1/4	743	30 1/4	768
12"	300	12	2 3/4	70	33 1/4	845	34 1/4	870

API 6A Installation and Stud Selection



API Installation Dimensions - Class 2000

Size in	A		B		C		Weight	
	in	mm	in	mm	in	mm	lbs.	kg.
2 1/16"	4 3/8	143	2 3/4	70	1 1/16	43	14	6
2 9/16"	5 1/8	130	3 1/4	83	2 1/8	54	16	7
3 1/8"	5 7/8	149	3 1/4	83	2 3/8	67	24	11
4 1/16"	7 5/8	194	4	102	3 7/16	87	40	18
7 1/16"	10 1/2	267	6 1/4	159	5 3/16	132	115	52
9"	12 5/8	321	8 1/8	206	6 13/16	173	229	104
11"	15 3/4	400	9 1/2	241	8 1/2	216	388	176
13 5/8"	18	457	11 1/2	292	10 1/8	257	540	245

NOTES: Dimensions for 10000 and 15000 ratings available on request.


Allowable leakage rates for API 6A (also API 6D) metal seated valves in accordance with API 598.

API Installation Dimensions - Class 3000

Size in	A		B		C		Weight	
	in	mm	in	mm	in	mm	lbs.	kg.
2 1/16"	5 5/8	143	2 3/4	70	1 11/16	43	14	6
2 9/16"	6 1/2	165	3 1/4	83	2 1/8	54	16	7
3 1/8"	6 7/8	168	3 1/4	83	2 5/8	67	25	11
4 1/16"	8 1/8	206	4	102	3 7/16	87	43	20
7 1/16"	11 3/8	289	6 1/4	159	5 3/16	132	110	50
9"	14 1/8	359	8 1/8	206	6 13/16	173	219	99
11"	17 1/8	435	9 3/4	248	8 1/2	216	397	180
13 5/8"	19 5/8	498	12	305	10 1/8	257	725	329

API Installation Dimensions - Class 5000

Size in	A		B		C		Weight	
	in	mm	in	mm	in	mm	lbs.	kg.
2 1/16"	5 5/8	143	2 3/4	70	1 11/16	43	15	7
2 9/16"	6 1/2	165	3 1/4	83	2 1/8	54	22	10
3 1/8"	6 7/8	175	3 3/8	86	2 5/8	67	31	14
4 1/16"	8 1/4	210	4 1/8	105	3 7/16	87	49	22
7 1/16"	11 1/8	283	6 1/4	159	5 3/16	132	190	86
9"	13 1/8	352	8 1/8	206	6 13/16	173	285	129
11"	17 1/8	435	10	254	8 1/2	216	502	228



API Stud Selection - Class 2000

Size in	No. of Studs	B		C	
		in	mm	in	mm
2 1/16"	8	5/8	16	8	203
2 9/16"	8	3/4	19	9	229
3 1/8"	8	3/4	19	9 1/2	241
4 1/16"	8	7/8	22	11 1/2	292
7 1/16"	12	1	25	14	356
9"	12	1 1/8	29	17	432
11"	16	1 1/4	32	19	483
13 5/8"	20	1 1/4	32	23 3/4	546

API Stud Selection - Class 3000

Size in	No. of Studs	B		C	
		in	mm	in	mm
2 1/16"	8	7/8	22	9 1/4	235
2 9/16"	8	1	25	11 1/4	286
3 1/8"	8	7/8	22	11 1/2	292
4 1/16"	8	1 1/8	29	12	305
7 1/16"	12	1 1/8	29	15 1/4	387
9"	12	1 1/8	35	18 3/4	476
11"	16	1 3/8	35	20	508
13 5/8"	20	1 1/8	35	21 1/2	591


API Stud Selection - Class 5000

Size in	No. of Studs	B		C	
		in	mm	in	mm
2 1/16"	8	7/8	22	9 1/4	235
2 9/16"	8	1	25	11 1/4	286
3 1/8"	8	1 1/8	29	12	305
4 1/16"	8	1 1/4	32	13	330
7 1/16"	12	1 3/8	35	18 3/4	476
9"	12	1 5/8	41	21	533
11"	12	1 7/8	48	24 1/2	622


Style X Extended Body Wafer Check Valves

The "Extended Body" version of the Duo-Chek was designed for extremely fast opening conditions. These types of applications are generally associated with compressed gas or steam that causes damage from the explosive opening effect on the closure mechanism. This damage can render them inoperative. This is especially true with slow response valves such as swing and titling disc check valves.

The Style X body design has special geometry and plate configuration to allow each plate to strike the stop pin in its center of percussion. To absorb high impacts, the stop pin and hinge lugs are oversized.



Typical applications include centrifugal compressor discharge where compressors are subject to "surging", air separation plants, pipelines where compressors are mounted in parallel, and steam extraction. Style X Duo-Chek valves are generally not required for liquid applications.



Installation Dimensions - Pressure Classes 150–2500

ASME Class 150

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
6"	150	8 3/4	222	4 13/16	122	6 3/8	168	46	21
8"	200	11	279	6 1/4	159	8 5/8	219	91	41
10"	250	13 3/8	340	7 1/4	184	10 3/4	273	166	75
12"	300	16 1/8	410	9	229	12 3/4	324	244	111
14"	350	17 3/4	451	8 7/8	213	14	356	260	118
16"	400	20 1/4	514	9 1/2	241	16	406	345	157
18"	450	21 5/8	549	10 3/8	264	18	457	427	194
20"	500	23 7/8	606	11 3/4	298	20	508	548	249
24"	600	28 1/4	718	13 3/4	349	24	610	874	396
26"	650	30 1/2	775	18	457	26	660	1741	790
30"	750	34 3/4	883	18	457	30	762	1544	700
32"	800	37	940	20 7/8	530	32	813	1638	743
36"	900	41 1/4	1048	21 7/8	556	36	914	2750	1247
42"	1050	48	1219	25 3/4	654	42	1067	3862	1752
48"	1200	54 1/2	1384	30 7/8	784	48	1219	6000	2722
54"	1350	61	1550	32 3/4	832	54	1372	7462	3385

ASME Class 300

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
6"	150	9 7/8	251	4 13/16	122	6 5/8	168	61	28
8"	200	12 1/8	308	6 1/4	159	8 5/8	219	107	48
10"	250	14 1/4	362	7 1/4	184	10 3/4	273	166	75
12"	300	16 5/8	422	9	229	12 3/4	324	244	111
14"	350	19 1/8	486	10 1/4	260	14	356	407	185
16"	400	21 1/4	540	11 1/8	283	16	406	533	242
18"	450	23 1/2	597	12 1/2	318	18	457	698	317
20"	500	25 3/4	654	13 3/4	349	20	508	900	408
24"	600	30 1/2	775	16	406	24	610	1446	656
28"	700	35 7/8	911	20 1/4	514	28	711	1992	904
30"	750	37 1/2	953	20 5/8	524	30	762	2457	1115
36"	900	44	1118	25	635	36	914	3947	1790
42"	1050	50 3/4	1289	31 7/8	810	42	1067	6523	2959
48"	1200	58 3/4	1492	35	889	48	1219	7483	3394

Consult factory for additional sizes and pressure classes.

ASME Class 600

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
8"	200	12 5/8	321	7 1/2	191	8 5/8	219	178	81
10"	250	15 1/4	400	9 7/8	251	10 3/4	273	285	130
12"	300	18	457	11 5/8	295	12 3/4	324	366	166
14"	350	19 3/8	492	12 3/4	324	14	356	485	220
16"	400	22 1/4	565	14 1/2	368	16	406	705	320
18"	450	24 1/6	613	16 3/4	425	18	457	1057	480
20"	500	26 7/8	683	17 1/2	445	20	508	1531	695
24"	600	31 1/8	791	21 1/4	540	24	610	2240	1016
28"	700	36	914	23	584	28	711	3277	1486
30"	750	38 1/4	972	26 3/4	680	30	762	3746	1699
36"	900	44 1/2	1130	31	787	36	914	7000	3175
48"	1200	54 3/4	1391	40 1/8	1019	48	1219	9972	4523

ASME Class 900

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
6"	150	11 5/8	289	6 7/8	175	6 3/4	171	149	68
10"	250	17 1/8	435	10 1/4	260	10 3/4	273	462	210
12"	300	19 5/8	498	12 13/16	325	12 3/4	324	605	274
14"	350	20 1/2	521	14 5/8	371	14	356	1030	467
16"	400	22 2/8	575	15 1/2	394	16	406	1553	705
20"	500	27 1/2	699	19 1/2	495	20	508	1583	718
24"	600	33	838	22 1/4	565	24	610	3029	1374
30"	750	39 3/4	1010	28 7/8	734	30	762	6310	2862



ASME Class 1500

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
10"	250	17 1/8	435	11 1/2	292	10 3/4	273	476	216
12"	300	20 1/2	521	13 7/8	353	12 3/4	324	805	365
14"	350	22 2/4	578	14 1/8	371	14	356	1080	490
16"	400	25 1/4	641	16 1/2	419	16	406	1530	694
18"	450	27 3/4	705	20 1/4	514	18	457	2109	957
20"	500	29 3/4	756	21 1/8	556	20	508	2376	1077
24"	600	35 1/2	902	24 1/8	632	24	610	4329	1964

ASME Class 2500

Size		A		B		C		Weight	
in	mm	in	mm	in	mm	in	mm	lbs.	kg.
10"	250	18 3/4	476	11 1/2	292	10 3/4	273	577	262
12"	300	21 5/8	549	13 7/8	352	12 3/4	324	598	271

Style X Stud Selection – Pressure Classes 150–2500



ASME Stud Selection Class 150

Valve Size		No. of Studs	B		C		D	
			Bolt Diameter	Raised Face	in	mm	in	mm
in	mm							
6"	150	8	3/4	19	9	229	9 1/2	241
8"	200	8	3/4	19	10 3/4	273	11 1/4	286
10"	250	12	7/8	22	12	305	12 1/2	318
12"	300	12	7/8	22	14	356	14 1/2	368
14"	350	12	1	25	14	356	14 1/2	368
16"	400	16	3/4	19	14 3/4	375	15 1/4	387
18"	450	16	1 1/8	29	16 3/8	425	17 1/4	438
20"	500	20	1 1/8	29	18 1/4	464	18 3/4	476
24"	600	20	1 1/4	29	20 3/4	527	21 1/4	540
26"	650	24	1 1/4	32	26 3/4	679	27 1/4	692
30"	750	28	1 1/4	32	27 1/4	692	27 3/4	705
32"	800	28	1 1/2	38	32	1690	32 3/4	832
36"	900	32	1 1/2	32	32 1/4	819	32 3/4	832
42"	1050	36	1 1/2	38	37 1/4	946	-	-
48"	1200	44	1 1/2	38	43 1/4	1099	-	-
54"	1350	44	1 3/4	44	43 1/2	1105	-	-

ASME Stud Selection Class 300

Valve Size		No. of Studs	B		C		D	
			Bolt Diameter	Raised Face	in	mm	in	mm
in	mm							
6"	150	12	3/4	19	10	254	10 3/4	273
8"	200	12	7/8	22	11 3/4	298	12 1/2	318
10"	250	16	1	25	13 3/4	349	14 1/2	368
12"	300	16	1 1/8	29	16	406	16 3/4	425
14"	350	20	1 1/8	29	17 1/2	445	18 1/4	464
16"	400	20	7/8	22	18 1/2	470	19	483
18"	450	24	1 1/4	32	20 3/4	527	21 1/2	546
20"	500	24	1 1/4	32	22	641	22 3/4	578
24"	600	24	1 1/2	29	15 1/4	648	26 1/4	667
28"	700	28	1 5/8	41	31	787	31 1/2	800
30"	750	28	1 3/4	44	32 1/4	819	33 1/2	851
36"	900	32	2	51	38 1/2	978	-	-
42"	1050	32	2	51	47 1/2	1206	-	-
48"	1200	40	2	51	50 1/4	1276	-	-

ASME Stud Selection Class 600

Valve Size		No. of Studs	B		C		D	
			Bolt Diameter	Raised Face	in	mm	in	mm
in	mm							
8"	200	12	1 1/8	29	15 1/4	387	15 1/4	387
10"	250	16	1 1/4	32	18 1/4	464	18 3/4	476
12"	300	20	1 1/4	32	20 1/2	521	20 3/4	527
14"	350	20	1 3/8	35	22	559	22	559
16"	400	20	1 1/8	29	24 1/2	622	24 1/2	622
18"	450	20	1 1/8	41	30	762	30 1/4	768
20"	500	24	1 5/8	41	29	737	29 1/2	743
24"	600	24	1 7/8	48	34 1/4	870	34 3/4	883
28"	700	28	2	51	36 1/2	927	37	940
30"	750	28	2	51	42	1067	42 1/2	1080
36"	900	28	2 1/2	64	47	1194	-	-
48"	1050	32	2 3/4	70	62	1574	-	-

ASME Stud Selection Class 900

Valve Size		No. of Studs	B		C		D	
			Bolt Diameter	Raised Face	in	mm	in	mm
in	mm							
6"	150	12	1 1/8	29	14 3/4	375	15	381
10"	250	16	1 3/8	35	19 1/2	495	19 3/4	502
12"	300	20	1 3/8	35	23	584	23 1/4	591
14"	350	20	1 1/2	38	25 3/4	654	26 1/4	667
16"	400	20	1 1/4	32	26 3/4	679	27	686
20"	500	20	2	51	33 1/4	844	34	864
24"	600	20	2 1/2	64	39 3/4	1010	40 3/4	1035
30"	750	20	3	76	48	1219	48 1/2	1232


ASME Stud Selection Class 1500

Valve Size		No. of Studs	B		C		D	
			Bolt Diameter	Raised Face	in	mm	in	mm
in	mm							
10"	250	12	1 7/8	48	25	635	25 1/4	641
12"	300	16	2	51	29	737	29 1/2	749
14"	350	16	2 1/4	57	31 1/4	794	32 1/4	819
16"	400	16	1 1/2	38	34	864	35	889
18"	450	16	2 3/4	70	39 3/4	1010	41	1041
20"	500	16	3	76	43	1092	44	1118
24"	600	16	3 1/2	89	49	1245	49 1/4	1251

ASME Stud Selection Class 2500


Valve Size		No. of Studs	B		C		D	
			Bolt Diameter	Raised Face	in	mm	in	mm
in	mm							
10"	250	12	2 1/2	64	31	787	31 3/4	806
12"	300	12	2 3/4	70	35 1/2	902	36 1/2	927

Duo-Chek Specials



Grayloc® Hub End Valves

Valves with Grayloc ends may be furnished for use with hub end, clamp-style connections. These end connections simplify installation procedures in systems that utilize them. Please contact your sales office for information regarding sizes and pressure ratings available, and other hub end connections such as Spolock, Seaboard Lloyd, etc.



Cryogenic Valves

Duo-Chek valves may be furnished for subatmospheric to cryogenic temperatures (-50°F through -450°F). Special materials of construction such as low temperature alloy steels, austenitic stainless steel, aluminum bronze or monel are generally required.



Butt Weld Valves

Valves with butt weld ends may be furnished for piping systems designed for welded system components to eliminate potential joint leak paths. See Ordering Information for proper figure number designation, so that weld-end preparations match the mating pipe schedules.



Coated & Lined Valves

Duo-Chek valves may be furnished with linings, when specified, for abrasion or corrosion resistance. Linings include Natural Rubber, Neoprene, and others. All body surfaces of lined valves are covered with the specified material, eliminating the need for gaskets. Hinge and stop pin holes are encapsulated to seal them against line fluids. Solid alloy valves are recommended for extremely corrosive applications. A variety of coatings may be provided on request to resist corrosion or abrasion. Some of the commonly specified coatings include epoxies, coal tar derivatives and sacrificial zinc primers. Please discuss your requirements with your sales office.

Other Specials

Other Duo-Chek specials furnished include:

- Valves to comply with NACE MR-01-75
- Valves cleaned for liquid oxygen (LOX) service
- Valves prepared for Food Service (austenitic stainless steel)
- Special testing for valves, including radiography, magnetic particle, dye penetrant, ultrasonic, helium leak, etc.

Technical Data

**ASME B16.34 Pressure-Temperature Ratings
Steel and Stainless Steel**

Temperature		Maximum Non-Shock Service Pressure, psi and kg/cm ² (ASME B16.34)									
°C	°F	Class 150					Class 300				
		Steel (1) (2)		Steel (1) (3)		316SS	Steel (1) (2)		Steel (1) (3)		316SS
		kg/cm ²	psi	kg/cm ²	psi	kg/cm ²	psi	kg/cm ²	psi	kg/cm ²	psi
-29 to 0	-20 to 32	20.0	285	-	-	19.3	275	52.0	740	-	-
0 to 38	32 to 100	20.0	285	20.0	285	19.3	275	52.0	740	52.0	740
93	200	18.3	260	18.3	260	16.5	235	47.8	680	47.8	680
149	300	16.2	230	16.2	230	15.1	215	46.0	655	46.0	655
204	400	14.1	200	14.1	200	13.7	195	44.6	635	44.6	635
260	500	12.0	170	12.0	170	12.0	170	42.5	605	42.5	605
316	600	9.8	140	9.8	140	9.8	140	40.1	570	40.1	570
343	650	8.8	125	8.8	125	8.8	125	38.7	550	38.7	550
371	700	7.7	110	7.7	110	7.7	110	37.3	530	37.3	530
399	750	6.7	95	6.7	95	6.7	95	35.5	505	35.5	505
427	800	5.6	80	5.6	80	5.6	80	28.8	410	28.8	410
454	850	4.6	65	4.6	65	4.6	65	22.5	320	22.5	320
482	900	3.5	50	3.5	50	3.5	50	16.2	230	16.2	230
510	950	2.5	35	2.5	35	2.5	35	9.5	135	9.5	135
538	1000	1.4	20	1.4	20	1.4	20	6.0	85	6.0	85
Hydrostatic Shell Test		31.6	450	31.6	450	29.9	425	79.1	1125	79.1	1125
°C	°F	Class 600					Class 900				
-29 to 0	-20 to 32	104.0	1480	-	-	101.2	1440	156.1	2220	-	-
0 to 38	32 to 100	104.0	1480	104.0	1480	101.2	1440	156.1	2220	156.1	2220
93	200	95.6	1360	95.6	1360	87.2	1240	143.1	2035	143.1	2035
149	300	92.1	1310	92.1	1310	78.7	1120	138.1	1965	138.1	1965
204	400	88.9	1265	88.9	1265	72.1	1025	133.6	1900	133.6	1900
260	500	84.7	1205	84.7	1205	67.1	955	127.2	1810	127.2	1810
316	600	79.8	1135	79.8	1135	63.3	900	119.9	1705	119.9	1705
343	650	77.3	1100	77.3	1100	62.2	885	111.8	1650	111.8	1650
371	700	74.5	1060	74.5	1060	61.2	870	112.5	1590	112.5	1590
399	750	71.4	1015	71.4	1015	60.1	855	106.9	1520	106.9	1520
427	800	58.0	825	58.0	825	59.4	845	86.8	1235	86.8	1235
454	850	45.0	640	45.0	640	58.7	835	67.1	955	67.1	955
482	900	32.3	460	32.3	460	58.3	830	48.5	690	48.5	690
510	950	19.3	275	19.3	275	54.5	775	28.8	410	28.8	410
538	1000	12.0	170	12.0	170	51.0	725	17.9	255	17.9	255
Hydrostatic Shell Test		156.4	2225	156.4	2225	152.9	2175	235.5	3350	235.5	3350
°C	°F	Class 1500					Class 2500				
-29 to 0	-20 to 32	260.5	3705	-	-	253.1	3600	433.8	6170	-	-
0 to 38	32 to 100	260.5	3705	260.5	3705	253.1	3600	433.8	6170	433.8	6170
93	200	238.7	3395	238.7	3395	217.6	3095	397.5	5655	397.5	5655
149	300	229.9	3270	229.9	3270	196.5	2795	383.1	5450	383.1	5450
204	400	222.9	3170	222.9	3170	180.7	2570	371.2	5280	371.2	5280
260	500	212.0	3015	212.0	3015	168.0	2390	353.3	5025	353.3	5025
316	600	199.7	2840	199.7	2840	158.5	2255	332.5	4730	332.5	4730
343	650	193.0	2745	193.0	2745	155.4	2210	321.6	4575	321.6	4575
371	700	187.3	2665	187.3	2665	152.6	2170	311.1	4425	311.1	4425
399	750	178.2	2535	178.2	2535	150.1	2135	297.4	4230	297.4	4230
427	800	144.5	2055	144.5	2055	148.3	2110	241.1	3430	241.1	3430
454	850	112.1	1595	112.1	1595	146.9	2090	186.6	2655	186.6	2655
482	900	80.8	1150	80.8	1150	145.9	2075	134.6	1915	134.6	1915
510	950	48.2	685	48.2	685	135.7	1930	80.5	1145	80.5	1145
538	1000	30.2	430	30.2	430	127.9	1820	50.3	715	50.3	715
Hydrostatic Shell Test		391.9	5575	391.9	5575	379.6	5400	652.0	9275	652.0	9275

Notes:

For latest information please refer to ASME B16.34.

(1) Permissible, but not recommended for prolonged use above 800°F (427°C)

(2) CE impact tested material and standard non impact tested material

(3) CE non impact tested material

Technical Data

Valve Coefficient Cv

Valve Size		Class 125-300
in	mm	
2"	50	75
2 1/2"	65	95
3"	80	191
4"	100	377
5"	127	483
6"	150	821
8"	200	1,590
10"	250	2,920
12"	300	4,470
14"	350	5,870
16"	400	8,690
18"	450	10,940
20"	500	14,290
24"	600	23,000
30"	750	37,200
36"	900	59,000
42"	1050	92,000
48"	1200	126,000
54"	1350	186,000
60"	1500	217,000
66"	1650	280,000
72"	1800	350,000

Class 150 Spring Cracking Pressure (PSI)

Valve Size		Std. Torque	Low Torque	Min. Torque
in	mm			
2"	50	0.23	0.13	0.05
2 1/2"	65	0.26	0.12	0.04
3"	80	0.21	0.16	0.04
4"	100	0.22	0.11	0.05
5"	127	0.18	0.09	0.05
6"	150	0.14	0.07	0.04
8"	200	0.19	0.10	0.04
10"	250	0.18	0.10	0.04
12"	300	0.17	0.07	0.04
14"	350	0.15	0.06	0.04
16"	400	0.16	0.08	0.03
18"	450	0.15	0.07	0.03
20"	500	0.13	0.06	0.03
24"	600	0.10	0.05	0.03
30"	750	0.08	—	—
36"	900	0.08	—	—
42"	1050	0.05	—	—
48"	1200	0.06	—	—

- Spring cracking pressure is an estimate of the pressure required to overcome the spring force when valve is closed. This is not exact as valve cannot be used as a relief valve. The use of low and min. torque springs could effect the valve performance and should only be used when unique service conditions are evaluated.
- Valves 6" and larger have independent springs.

Spring & Drain Size Information

Spring Selection Guide

Spring Material	Operating Temperature Range	
	°C	°F
Type 316 S.S.	-129 to 120	-200 to 250
Inconel 600	-250 to 315	-420 to 600
Inconel X-750	-250 to 537	-420 to 1000

- Spring materials are included in trim materials as an important part of materials selection. The most common standard trim materials are shown under Ordering Information.
- For unique service conditions, different torque springs as well as other spring materials are available. Please consult factory.

Body Drain Hole Sizes
(Available when specified)


ASME Class 125 (Cast Iron) Schedule A	
2" - 8"	1/8"
(50mm – 200mm)	(3.18mm)
10" – 12"	3/8"
(250mm – 300mm)	(9.52mm)
14" & up	3/4"
(350mm & up)	(19.1mm)
ASME Class 150-2500 Schedule B	
2" - 2 1/2"	1/4"
(50mm – 65mm)	(6.35mm)
3" - 4"	3/8"
(75mm – 100mm)	(9.52mm)
5"	1/2"
(125mm)	(12.7mm)
6" & up	3/4"
(150 mm)	(19.1mm)

- All drain holes are located on the downstream side of the valve.

Technical Data

Pressure Loss Information

- The curves show pressure drops available with standard torque springs and the Duo-Chek in horizontal flow.
- Duo-Chek valves should be installed in horizontal flow with pins vertical for best performance. For other installations, contact the factory.
- Each piping system has a unique geometry which should be evaluated whenever the liquid media velocity exceeds 8 feet/second (2.4m/sec) through a swage or expansion (15° or greater included angle) directly upstream of the valve. Where practicable, **for maximum service life, and based on actual service**, a minimum of one (1) to five (5) pipe diameters distance should be maintained between the valve and the pump discharge and pipe fittings (swages or expansion).
- Systems with drastic flow decelerations may require higher torque springs for faster valve response and to reduce water hammer. Please consult the factory.
- We can evaluate Duo-Chek valves relative to your system behavior.



Ordering Information

Figure Number System

Size	Style	Pressure Class	Body & Plate	Seal	End Connection	Body Configuration	Modification Number
24"	H	15	S	P	F	3	- 9

DESCRIPTION: 24" Style H, ASME Class 150, Carbon Steel Body and Plates, Metal Seal, raised face flanges, with double flange body, (modification number indicates Inconel X spring)

Valve Size
Nominal valve sizes are expressed in inches or millimeters.
In Inches: For use with ASME, API and BS Flange Standards.
In Millimeters: For use with DIN, AS or JIS rated valves (size preceded by "M" for DIN, "A" for AS or "J" for JIS).

Style		
Ordering Letter	Body Type	Size Range
G	Standard Design, Wafer	2" through 72" (50mm through 1800mm)
H	Retainerless Duo-Chek Design Wafer, Lug or Double Flange	2" through 72" (50mm through 1800mm)
X	Extended Body Design	6" through 54" (152mm through 1300mm)
U	Underwriters' Laboratories Listed Valves for Fire Protection Service	4" through 12" (except 5") (U12 HMP Valves Only)
W*	Bodies with Integral Weld-Ends	2" through 72" (50mm through 1800mm)

*Weld-end valves also require the additional designation of the pipe schedule they are designed to fit.

ASME		API ^A		DIN / JIS ¹		BS / AS ²	
Ordering No.	Class	Ordering No.	Class	Ordering No.	PN Rating	Ordering No.	Table
12	125	21	2000	Flange Standard:	6		
15	150				10	B - BS	A
25	250	31	3000	M - DIN	16		thru T
30	300				25	A - AS	
40	400	51	5000	J - JIS	40		
60	600				64		
90	900	101	10000		100		
150	1500				160		
250	2500	151	15000		250		
450	4500				320		

Δ API Class is shown in psig, cold working pressure.

1 Metric valves with DIN or JIS standard flanges are designated by having the nominal size expressed in millimeters, preceded by "M" or "J". Flange ratings in PN numbers are then listed after the valve style, as in ASME or API Valves.

Example: M 100 (4") G16 SPF

Flange Standard
(M - DIN)
100mm Size

Pressure Rating, PN
for DIN or JIS
(in bars)

This specifies a metric valve, designed to fit between DIN flanges. Nominal size is 100 millimeters (corresponding to 4"), Style G Duo-Chek with a pressure rating of 16 bars, carbon steel body and plate, metal seat, and raised face end connections.

2 Valves designed for use with British Standard 10 or Australian Standard 2129 are defined by adding two letters between the style of construction and pressure rating. First letter designates the standard, and the second letter denotes the table in that standard.

Example: 6" G B E 15 BNF

Flange Standard
B - British Std. 10

ASME Class
is made from
Table in corresponding
Standard

Figure number lists a 6" Style G Duo-Chek, designed to fit between British Standard 10, Table E Flanges, using a Class 150 Valve, having an aluminum bronze body and plates, Neoprene seal and raised face end connections.

Ordering Information

Body and Plates					
Ordering Letter	Material	Specification	Ordering Letter	Material	Specification
B	Aluminum Bronze	ASTM B148, Alloy 952	T	317 S.S.	ASTM A351, Gr. CG-8M
AB	Ni-Aluminum Bronze	ASTM B148, Alloy 958	U	WC6 Alloy Steel	ASTM A217, Gr. WC6 (1¼ Cr)
C	316 Stainless Steel	ASTM A351, Gr. CF-8M	V	347 S.S.	ASTM A351, Gr. CF-8C
E	410 Stainless Steel	ASTM A217, Gr. CA15 (12% Cr)	Y	C5 Alloy Steel	ASTM A217, Gr. C5 (5% Cr)
F	Alloy 20	ASTM A351, Gr. CN7M	Z	WC9 Alloy Steel	ASTM A217, Gr. WC9 (2½ Cr)
G	Low Temp. C.S.	ASTM A352, Gr. LCB	CA	Duplex	ASTM A351, Gr. CD4MCu
H	Cast Iron with Al. Br. Plates	ASTM A126, class 40	DZ	22% Duplex	UNS S31803, ASTM A890, Gr. 4A
K	Hastelloy® C	ASTM B148, (952)	EA	254 SMO Stainless	UNS S31254, (ASTM CK3MCuN)
L	C12 Alloy Steel	A494, Gr. CW12MW	FN	Inconel® 625	ASTM A494, Gr. CW-6MC
M	Monel	ASTM A217, Gr. C12 (9% Cr)	GC	LCC Low Temp. Steel	ASTM A352, Gr. LCC
S	Carbon Steel (Std. and CE non-impact tested)	ASTM A494, Gr. M30C	TT	Titanium	ASTM B367, Gr. C2/ASTM B348, Gr 2r
S1	Carbon Steel (CE impact tested)	ASTM A216, Gr. WCB	EB	25% Super Duplex	ASTM A890, Gr 6A/A351, Gr. CD3MWCuN
		ASTM A216, Gr. WCB			

Seal*			End Connections		Special Body Configurations		
Ordering Letter	Material	Operating Temperature		Ordering Letter	Connections	Designation No.	Configuration
		°C	°F				
A	EPDM	-54 to 149	-65 to 300	F	Serrated face	None (Blank)	Wafer Style, inserted between mating flanges with studs spanning entire length
B3	EPDM (NSF-61)	-54 to 149	-65 to 300	G	Grayloc® Hub	1	Lug design w/threaded holes bolted from each end
M	Buna-N	-57 to 121	-70 to 250	P	Plain Face (non serrated)	2	Lug design with through-bolt holes to protect studs
N	Neoprene	-40 to 121	-40 to 250	R	Ring Joint	3	Double flanged design with valve flanges bolted to individual line flanges
P	As Body	-29 to 538	-20 to 1000	W	Weld-End		
S	Silicone	-101 to 260	-150 to 500				
U	Refrigeration Grade	-40 to 121	-40 to 250				
V	Viton-B®	-29 to 204	-20 to 400				

* This range of operating temperatures is for general guidance. The range varies with application, body and plate material.

® Viton is a registered name of DuPont.

Common Modifications					
Mod. No.	Material Description	Mod. No.	API Trim No.	Material Description	
-9	Inconel X-750 Springs	-169	1	Type 410	
-14	316 S.S. Plate, Pins	-491	5	Hard Faced	
-39	410 S.S. Plate, Pins & Inconel X-750 Springs	-131E	8	F6 and Hard Faced	
-201	316 S.S. Plate, Pins, Inconel X-750 Springs	-772	9	Monel	
-233	316 S.S. Plate, Pins, Inconel X-750 Springs and 316 S.S. Overlay Seat	-233	10	Type 316	
-169	410 S.S. Plate, Pins, Inconel X-750 Springs and 410 S.S. Overlay Seat	-385E	12	316 and Hard Faced	
-772	Monel Plate, Pins, Springs, Bearings and Monel Overlay Seat				

Note: Numerous additional modifications may be specified. Please consult factory.

Standard trim (Wetted Parts) Materials						
Typical Figure No.	Body & Plate	Seal	Hinge Pin	Spring	Stop Pin	Retainer
BMF	Al. Bronze	Buna-N	316 S.S.	316 S.S.	316 S.S.	316 S.S.
CMF	316 Stainless	Buna-N	316 S.S.	316 S.S.	316 S.S.	316 S.S.
CPF	316 Stainless	316 Stainless	316 S.S.	Inconel 600	316 S.S.	316 S.S.
CVF	316 Stainless	Viton-B®	316 S.S.	Inconel 600	316 S.S.	316 S.S.
EPF	410 Stainless	410 Stainless	410 S.S.	Inconel 600	410 S.S.	410 S.S.
SMF	Carbon Steel	Buna-N	316 S.S.	316 S.S.	316 S.S.	Steel
SPF	Carbon Steel	Carbon Steel	316 S.S.	Inconel 600	316 S.S.	Steel
SVF	Carbon Steel	Viton-B®	316 S.S.	Inconel 600	316 S.S.	Steel

Additional Products

Uni-Chek[®]


Single-Disc Check Valves

- Sizes 2" – 36"
- ASME Classes 125–300
- Flanged, Plain, or Serrated Ends
- Cast Iron, Carbon Steel, and Stainless Steel
- Variety of external shaft options available



UL Valves

Underwriters Laboratories, Inc. approve and list the 4", 6", 8", 10" and 12" Figure U12 HMP Duo-Chek Valves for 250 psi service in fire protection systems.



DUO-CHEK®

Conroe, Texas Operations

9860 Johnson Road
Montgomery, Texas 77316
Tel: 936-588-8350
Fax: 936-588-8381

Thomastown, Australia Operations

322 Settlement Road
Thomastown, VIC 3074
Tel: +613-9465-2755
Fax: +613-9466-1365

Global Headquarters

9200 New Trails Drive, Suite 200
The Woodlands, Texas 77381-5219
Tel: 281-298-5463
Fax: 281-298-1920

Belfast, Northern Ireland Operations

6 Alexander Road
Cregagh, Belfast BT6 9HJ
Tel: +442-890-704222
Fax: +442-890-401582

www.craneenergy.com

Crane Energy Flow Solutions

CENTER LINE®

Resilient Seated Butterfly and Check Valves
Pneumatic and Electric Actuators

CRANE®

Cast Steel, Bronze, and Iron Valves

FLOWSEAL®

High Performance Butterfly Valves

JENKINS®

Bronze, Iron, and Cast Steel Valves

DUO-CHEK®

High Performance Wafer Check Valves

ALOYCO®

Corrosion Resistant Gate, Globe and Check Valves

UNI-CHEK®

Severe Service Check Valves

NOZ-CHEK® & COMPAC-NOZ®

Severe Service, Nozzle-Type Check Valves

PACIFIC®

High Pressure and Severe Service Valves
Quarter Turn Severe Service Plug Valves

WEDGEPLUG®

Severe Service, Metal-Seated Plug Valves

CRANE®

Energy Flow Solutions

Crane, Center Line, Flowseal, Duo-Chek, Uni-Chek, Pacific, Jenkins, Aloyco, Noz-Chek, Compac-Noz and Wedgeplug are all trademarks of Crane Co. ©2008