

SEE DRAWING NO. VM-22-M FOR STANDARD MATERIAL OF CONSTRUCTION.

VALVE	MODEL	INLET	OUTLET	MAX. W.P.	ORIFICE
SIZE	NO. **	SIZE	SIZE	P.S.I.	SIZE
1/2"_3/4" *	22.4	3/ ₄ " N.P.T.	1/2" N.P.T.	175	3/32"
1"	22.3	1" N.P.T.	¹ / ₂ " N.P.T.	175	3/32"
1/2"	22.7	1/2" N.P.T.	1/2" N.P.T.	300	1/16"
1/2"-3/4"-1" *	22.9	1" N.P.T.	1/2" N.P.T.	300	1/16"

^{*}When multiple size inlets are indicated for a specific model number, the valve is threaded for the largest size indicated and a reducer bushing is provided for the smaller sizes.

^{**}Add "H" to Model No. for optional screened hood SPK-5H.

1	BODY	11	ORIFICE BUTTON
)	COVER	12	PIVOT PIN

² 3 4 LEVER FRAME 13

Revised 4-13-04

AIR RELEASE VALVE	DATE 5-8-69
VAL MATIC® VALVE AND MANUFACTURING CORP.	DRWG. NO. VM-22

¹⁴ 17 SEAT

PIVOT PIN
PIN RETAINER (NOT SHOWN)
PIPE PLUG
FLOAT RETAINER
LOCATOR
SCREENED HOOD
LOCK WASHER FLOAT 5 6 7 GASKET COVER BOLT FLOAT ARM 21 23 34 10

AIR RELEASE VALVE

SERIES NO. 22

STANDARD MATERIALS OF CONSTRUCTION

PART NO.	PART NAME	MATERIAL
1	BODY	CAST IRON ASTM A126, CLASS B
2	COVER	CAST IRON ASTM A126, CLASS B
3	LEVER FRAME	STAINLESS STEEL T316, ASTM A240
4	SEAT	STAINLESS STEEL T316, ASTM A276
5	FLOAT	STAINLESS STEEL T316, ASTM A240
6	GASKET	COMPRESSED NON-ASBESTOS FIBER
7	COVER BOLT	ALLOY STEEL SAE, GRADE 5
10	FLOAT ARM	STAINLESS STEEL T316, ASTM A240
11	ORIFICE BUTTON	VITON
12	PIVOT PIN	STAINLESS STEEL T316, ASTM A479
13	PIN RETAINER	STAINLESS STEEL PH 15-7 MO
14	PIPE PLUG	STEEL
17	FLOAT RETAINER	STAINLESS STEEL T316, ASTM F879
21	LOCATOR	STAINLESS STEEL T316, ASTM F593
34	LOCK WASHER	STAINLESS STEEL T316, ASTM A240

NOTE: ALL SPECIFICATIONS AS LAST REVISED.

Revised 1-29-03

MATERIALS OF CONSTRUCTION DATE 5/8/69



DRWG. NO.

VM-22-M